



aart T 15 A [CodeNr. 13104]

The aart T 15 A is a self powered, bi-amped 2-Way high-performance multipurpose loudspeaker system system, designed for professional portable applications and installations demanding the ultimate in sound performance from a single enclosure.

With a 90° x 60° coverage pattern it combines very high output capability with excellent sound performance and impact.

It features a powerful 15" (380mm) /3" (75mm) voice coil LF drive unit, and a 1" (25mm) exit HF compression driver with a 1.75" voice coil for extended high frequency response.

The integrated high performance Class D 2-channel amplifier, with integrated 2-channel DSP, delivers outstanding dynamic and excellent headroom. The 4 DSP presets and clearly arranged Input - Output section enable high application flexibility.

The versatile aart T 15 A suits for speech and music applications as a stand-alone fullrange loudspeaker or MF/HF speaker in sound reinforcement systems.

Key features

- > High-class performance in a compact design
- > Class D bi-amped power module
- > User-rotatable, constant directivity 90° x 60° horn
- > Vertical and horizontal orientation
- > 4 DSP presets
- > Dual-band limiter
- > Two inputs with level control, XLR/6.3 Jack Combo , one with MIC/LINE switch and with high- resolution microphone pre-amplifiers (in MIC mode)
- > Line/Mix OUT switchable
- > Main and monitor operation possible
- > M8 inserts for flexible mounting options
- > Weight only 21 kg

Application

- > Portable sound reinforcement
- > Installation
- > Live Music
- > Bars and restaurants
- > Nightclubs
- > Stage monitoring
- > Corporate AV events and conferences

Recommended with

- > Subs:
SUB 18 A

For more informations please check our webside or contact us.

Specification

Loudspeaker Type	Self-powered, two-way bi-amped, multifunctional
Frequency Range (-10dB)	45 Hz - 20 kHz
Frequency Response (+- 3dB)	55 Hz - 18 kHz
Coverage Pattern	H 90° x V 60° nominal (user-rotatable)
Power Handling	500 W continuous, 2000 W peak
System Sensitivity (1w/1m)	99 dB
Maximum SPL (Calculated at 1m)	125 dB continuous, 131 dB peak
HF Driver	1,75"voice coil, 1" exit compression driver
LF Driver	15", 3" voice coil neodym speaker aaCRAAFT
Crossover	Active / DSP
Protection	Dual-band limiter
Active Tuning / Features	4 DSP presets, 2 x Line/Mic IN level & switch, Line/Mix OUT
Enclosure	Multi-angle, 15 mm birch plywood
Finish	Black textured paint
Fittings	7x M8 inserts, 2x handle, pole-mount socket, U-bracket optional
Protective Grille	Black perforated steel with acoustic transparent foam backing
Connectors	2x XLR / 6.35 Jack Combo, 1x XLR
Dimensions mm (WxHxD)	430 x 690 x 440
Weight	21 kg

Druckfehler / Irrtümer vorbehalten / Limited liability on contents

SOLTON Acoustic GmbH & Co. KG

Oberer Mühlweg 6 | Pocking/Rottau | GERMANY | Phone: +49 (0) 85 31 / 91 38 80

Fax:+49 (0) 85 31 / 97 85 07 | Email: info@solton-acoustic.de | Web: www.solton.de