



M 12 CX [CodeNr. 11010]

The M 12 CX is a self-powered, bi-amped stage monitor and multipurpose fullrange loudspeaker. It has been designed for professional portable applications and installations, demanding the ultimate in sound performance from a single enclosure.

It features a powerful 12"/1" coaxial transducer in a compact multi-angle enclosure made of 15 mm birch plywood. The integrated high performance Class D 2-channel amplifier, with integrated 2-channel DSP with 4 Presets, delivers outstanding dynamic and excellent headroom.

The versatile M 12 CX could be a perfect choice as an excellent stage monitor, fullrange speaker, frontfill for larger stages or as delay speaker.

Key features

- > High SPL with smooth response
- > High performance 12"/1" coaxial transducer
- > Class D bi-amped power module
- > 90° radial coverage
- > Advanced 2-Channel DSP with 4 Presets
- > Dual band limiters
- > Multi-angle, light weight, compact design
- > Monitor and FOH operation possible
- > M8 Rigging points for flexible mounting options
- > Weight only 14.5 kg

Application

- > Stage monitoring
- > Live Music
- > Portable sound reinforcement
- > Bars and restaurants
- > Nightclubs
- > Corporate AV events and conferences
- > Installation

Recommended with

- > Subs:
SUB 15 A, SUB 18 A

For more informations please check our webside or contact us.



Specification

Loudspeaker Type	Self-powered, Coaxial 12", Monitor/ Multipurpose
Frequency Range (-10dB)	50 Hz - 20 kHz
Frequency Response (+- 3dB)	55 Hz - 18 kHz
Coverage Pattern	H 90° x V 60° nominal
Power Handling	350 W continuous, 1400 W peak
System Sensitivity (1w/1m)	96 dB
Maximum SPL (Calculated at 1m)	121 dB continuous, 127 dB peak
HF Driver	1" exit compression driver
LF Driver	12" coaxial transducer
Crossover	Active / DSP
Protection	Dual-band limiter
Active Tuning / Features	DSP 4 Presets (Monitor 1/2, Basic, w.Sub), 2x Line/Mic IN level & switch, Chinch
Enclosure	Multi-angle, 15 mm birch plywood
Finish	Black polyurea coating
Fittings	3x handles, pole-mount socket, rigging points
Protective Grille	Black perforated steel with acoustic transparent foam
Connectors	Mic/Line, Chinch Input, Powercon Link, Loop Thru
Dimensions mm (WxHxD)	440 x 360 x 460
Weight	14.5 kg

Druckfehler / Irrtümer vorbehalten / Limited liability on contents

SOLTON Acoustic GmbH & Co. KG

Oberer Mühlweg 6 | Pocking/Rottau | GERMANY | Phone: +49 (0) 85 31 / 91 38 80

Fax:+49 (0) 85 31 / 97 85 07 | Email: info@solton-acoustic.de | Web: www.solton.de